

# FLEX SEAL

## TYPE SC

### Characteristics

- Elastomeric flexible coupling
- Stainless steel shear band
- Withstand up to 1.5 bar pressure
- Shear force resistant of up to 25 times the nominal bore



### Function

For use in sewerage, drainage and other non-pressure pipe systems to join or repair pipes of the same or different materials and diameters

In compliance with NF EN 476

### Range

Reference	Coupling reference	Ømini (mm)	Ømaxi (mm)	Width (mm)	Tightening (N.m)
6172209	SC65	57	65	102	6
6172212	SC90	75	90	102	6
6172215	SC115	100	115	102	6
6172218	SC137	120	137	120	6
6172221	SC150	130	150	120	6
6172224	SC175	150	175	120	6
6172225	SC200	175	200	150	10
6172227	SC225	200	225	150	10
6172230	SC250	225	250	150	10
6172233	SC275	250	275	150	10
6172236	SC290	265	290	190	10
6172239	SC335	310	335	190	10
6172243	SC365	340	365	190	10
6172245	SC410	385	410	190	13
6172246	SC430	400	430	190	13
6172248	SC510	480	510	190	13
6172251	SC525	495	525	190	13
6172254	SC620	590	620	190	13
6172255	SC635	605	365	190	13

